



Bluechip Hospitality services










Door No. 1/89 B Pillaiyar Koil Street,




Jalladianpet, Chennai- 600 100.

cell 9962605248 / 044-43204399, Gopal@bluechiph.com




GST # : 33AAQFB7004D1ZU

BLUECHIP CORELINE PRODUCTS


Red /Blue Round Isothermal Hot Box			
Ref No	Description	SPECIFICATION	Images
BHS-R-9L	New Insulated Container Round With SS inside and 4clips (Small) Stackable/ https://www.youtube.com/watch?v=5ibipMJ0-HI	Capacity Variants: 9 Ltrs Inner Dimensions / Diameter: 25cm x 21.5cm Outer Dimensions / Diameter: 28.5cm x 30 cm Height: 30cm, Weight of the Container: 3.1kg Temperature Drop/Hour: Each hour drop 4 degree. Color Availability: Red, MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane Insulation Thickness and Conductance: Insulated thickness 25mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-R-15L	Insulated Container Round with SS inside and 2clips Stackable https://www.youtube.com/watch?v=ZL_h08-5y4Y	Capacity Variants: 15 Ltrs Inner Dimensions / Diameter: 24cm x 27.5cm, Outer Dimensions / Diameter: 33.5cm x 30cm Height: 29cm, Weight of the Container: 4.2kg Temperature Drop/Hour: Each hour drop 4 degree. Color Availability: Red, MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane Insulation Thickness and Conductance: Insulated thickness 25mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-R-30L	New Insulated Container Round with SS inside and 4clips (Med) Stackable	Capacity Variants: 30 Ltrs Inner Dimensions / Diameter: 33cm x 33cm, Outer Dimensions / Diameter: 44.6cm x 35cm Height: 38cm, Weight of the Container: 6.7kg Temperature Drop/Hour: Each hour drop 4 degree. Color Availability: Red, MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane Insulation Thickness and Conductance: Insulated thickness 25mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-R-50L	Insulated Container Round with SS inside and 2clips (Large) Stackable	Capacity Variants: 50 Ltrs Inner Dimensions / Diameter: 39cm x 40cm, Outer Dimensions / Diameter: 46cm x 45cm Height: 45cm, Weight of the Container: 8.2kg Temperature Drop/Hour: Each hour drop 4 degree. Color Availability: Red, MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane Insulation Thickness and Conductance: Insulated thickness 25mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-R-60L	Isothermal Hot Box with SS Inner finish 60LTR	Capacity Variants: 60 Ltrs Inner Dimensions / Diameter: 51cm x 51cm Outer Dimensions / Diameter: 51cm x 50cm Height: 55cm, Weight of the Container: 6.0kg Color Availability: Red, Blue MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane Insulation Thickness and Conductance: Insulated thickness 19mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-RT-9L	9 Ltrs Barrel with tea barrel	Capacity Variants: 9 Ltrs Inner Dimensions / Diameter: 25cm x 21.5cm, Outer Dimensions / Diameter: 28.5cm x 30 cm Height: 30cm, Weight of the Container: 3.1kg Temperature Drop/Hour: Each hour drop 4 degree. Color Availability: Red with Tap, MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane Insulation Thickness and Conductance: Insulated thickness 25mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-RT-15L	15 Ltrs Barrel with tea barrel	Capacity Variants: 15 Ltrs Inner Dimensions / Diameter: 24cm x 27.5cm, Outer Dimensions / Diameter: 33.5cm x 30cm, Height: 29cm, Weight of the Container: 4.2kg Temperature Drop/Hour: Each hour drop 4 degree. Color Availability: Red with Tap, MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane, Insulation Thickness and Conductance: Insulated thickness 25mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-RT-30L	30 Ltrs Barrel with tea barrel	Capacity Variants: 30 Ltrs Inner Dimensions / Diameter: 33cm x 33cm, Outer Dimensions / Diameter: 44.6cm x 35cm Height: 38cm, Weight of the Container: 6.7kg Temperature Drop/Hour: Each hour drop 4 degree. Color Availability: Red with Tap, MOC Inside: 304 stainless steel MOC Outside: PE material, MOC Insulation: Polyurethane, Insulation Thickness and Conductance: Insulated thickness 25mm, Inner and Outer Layer Connected Method: Foam injection	
BHS-DR-7L	BEVERAGE BARREL – 7L	Capacity 7 Ltrs, PACKAGED SIZE: 440*240*390mm PACKAGED WEIGHT: 4.96kgs PRODUCT SIZE: 430*230*376mm PRODUCT WEIGHT: 4.4kgs MATERIAL: PE+PU+PE	













BHS-DR-10L	BEVERAGE BARREL – 10L	Capacity 10 Ltrs, PACKAGED SIZE: 430*240*475mm PACKAGED WEIGHT: 6.38kgs PRODUCT SIZE: 420*230*460mm PRODUCT WEIGHT: 5.75kgs MATERIAL: PE+PU+PE	
BHS-DR-20L	BEVERAGE BARREL – 20L	Capacity 20 Ltrs, PACKAGED SIZE: 435*305*685mm PACKAGED WEIGHT: 9.96kgs PRODUCT SIZE: 425*295*672mm PRODUCT WEIGHT: 9kgs MATERIAL: PE+PU+PE	
BHS-DR-45L	BEVERAGE BARREL – 45L	Capacity 45 Ltrs, PACKAGED SIZE: 555*430*645mm PACKAGED WEIGHT: 14.95kgs PRODUCT SIZE: 540*420*630mm PRODUCT WEIGHT: 13.6kgs MATERIAL: PE+PU+PE	

Red Round Isothermal Hot Box Spare parts

BHS-SS-9L	Insulated Container Inner SS Carrier Round	9 Ltrs	
BHS-SS-15L		15 Ltrs	
BHS-GK-9L	Gas Ket	9Ltr. Container	
BHS-GK-15L	Gas Ket	15Ltr. Container	
BHS-GK-30L	Gas Ket	30Ltr. Container	
BHS-GK-40L	Gas Ket	50Ltr. Container	
BHS-T	TAPS		
	Isothermal Stopper Vents		
	Square Barrel Lid Side Clip		
	Square Barrel Metal Side Clips		
	Gas Ket	SQUARE CONTAINER : 10Ltr	
	Gas Ket	SQUARE CONTAINER : 15Ltr	
	Gas Ket	SQUARE CONTAINER : 20Ltr	
	Gas Ket	SQUARE CONTAINER : 30Ltr	
	Gas Ket	SQUARE CONTAINER : 40Ltr	
	Gas Ket	SQUARE CONTAINER : 50Ltr	

SQUARE BARREL WITH WHEELS











BHS-SQW-10L	INSULATION SQUARE BARREL – 10L (With Wheels)	Insulated Container Square with Wheels SS inside and 4clips (Large) Stackable Capacity 10 Ltrs, Outer Dia: (L x B x H): 44 x 38.5 x 29 CM Inner Dia: (L x B x H): 36 x 30 x 15 CM	
-------------	--	---	---

BHS-SQW-15L	INSULATION SQUARE BARREL – 15L (With Wheels)	Insulated Container Square with Wheels SS inside and 4clips (Large) Stackable Capacity 15 Ltrs, Outer Dia: (L x B x H): 44 x 38.5 x 34 CM Inner Dia: (L x B x H): 36 x 30 x 20 CM	
BHS-SQW-20L	INSULATION SQUARE BARREL – 20L (With Wheels)	Insulated Container Square with Wheels SS inside and 4clips (Large) Stackable Capacity: 20L, Net Weight: 8KG, External Size: (L x B x H): 390*390*450mm Internal Size: (Dia): Φ280*280mm	
BHS-SQW-30L	INSULATION SQUARE BARREL – 30L (With Wheels)	Insulated Container Square with Wheels SS inside and 4clips (Large) Stackable Capacity: 20L, Net Weight: 8KG, External Size: (L x B x H): 390*390*450mm Internal Size: (Dia): Φ280*280mm	
BHS-SQW-40L	Insulated Container square with SS inside and 2clips (Large) Stackable (With Wheels)	Name: Insulated Container Square With Wheels External Dimension: 31.5*31.5*41.5cm Internal Dimension: 46*46*59cm Cart. Dimension: 47.5*47.5*60cm, Capacity: 45L N.W.: 12kgs, G.W.: 14kgs	
BHS-SQW-50L	Insulated Container square with SS inside and 2clips (Large) Stackable (With Wheels)	Capacity: 50 Ltrs Outer Size: 45.5 cm x 45.5 cm x 65 cm Inner Size: 34 cm x 34 cm x 44.5 cm Net Weight: 12.7 Kgs Packaged Weight: 14.2 Kgs Packaged Size: 46.5 cm x 48 cm x 67.5 cm	
BHS-UPC-Non-Electric Pan Carrier 90L	Pan Carrier Hot Cold Holding 90L Non Electric 6 Layers (Stackable)	Name: Insulated Food Pan Carrier External Dimension: 63.5*46*64CM Internal Dimension: 54.5*33.5*50CM Cart. Dimension: 64.5*46.5*64.5CM Capacity: 90L, N.W.: 13.5kgs G.W.: 14.5kgs, Usage: Loading GN Pan	
BHS-UPC-Non-Electric Pan Carrier 120L	Pan Carrier Hot Cold Holding 120L Non Electric 8 Layers (Stackable)	Name: Hot Boxes For Catering External Dimension: 61*42*80cm Internal Dimension: 53*33*65cm Cart. Dimension: 62.5*42.5*80.5cm Capacity: 120L, N.W.: 19kgs G.W.: 21kgs, Usage: Loading GN Pan	
Matt Pan	GN Pan 1/1	GN Pan 1/1 65 mm 530x325x65 mm Capacity 9.5 L	
Matt Lid	GN Lid 1/1	GN Lid 1/1 530x325 mm	
Grip Pan	GN Pan 1/1	GN Pan 1/1 65 mm 530x325x65 mm Capacity 9.5 L	
Grip Lid	GN Lid 1/1	GN Lid 1/1 530x325 mm	
BHS-UPC-Electric Pan Carrier 90L	Pan Carrier Hot Cold Holding 90L Electric 6 Layers (Stackable)	Outer Size: 62.5cm x 44.5cm x 76.5cm Inner Size: 54.5cm x 33.5cm x 63.5cm, Volume: 120L, Net Weight: 19.2Kgs, Packaged Weight: 21.2Kgs, Packaged Size: 63cm x 46cm x 77cm, Power Supply: 220V/50Hz, 1 Phase Input Power: 300Watt.	
Matt Pan	GN Pan 1/1	GN Pan 1/1 65 mm 530x325x65 mm Capacity 9.5 L	
Matt Lid	GN Lid 1/1	GN Lid 1/1 530x325 mm	
Grip Pan	GN Pan 1/1	GN Pan 1/1 65 mm 530x325x65 mm Capacity 9.5 L	
Grip Lid	GN Lid 1/1	GN Lid 1/1 530x325 mm	

BHS-TL-30L	ISOTHERMAL HOT BOXES FOR FOOD TRANSPORT	Outer size: 63 * 44 * 31.5 cm; Inner size: 53 * 33 * 21 cm; Volume: 30L; Net Weight: 9.5 kgs; Packaged Weight: 10.65 kgs; Packaged size: 64 cm * 45 cm * 34 cm;	
Matt Pan	GN Pan 1/1	GN Pan 1/1 200 mm 530x325x200 mm Capacity 28 L	
Matt Lid	GN Lid 1/1	GN Lid 1/1 530x325 mm	
Matt Pan	GN Pan 1/2	GN Pan 1/2 200 mm 325x265x200 mm Capacity 12 L	
Matt Lid	GN Lid 1/2	GN Lid 1/2 325x265 mm	
Matt Pan	GN Pan 1/3	GN Pan 1/3 200 mm 325x176x200 mm Capacity 7.5 L	
Matt Lid	GN Lid 1/3	GN Lid 1/3 325x176 mm	
ROTO MOULDED ICE BOX			
	Insulated Ice Box	Capacity 6 Litrs Outer Dia: (LxBxH) : 270 x 214 x 190 MM	
	Insulated Ice Boxes	Capacity 14 Litrs Outer Dia: (LxBxH) : 350 x 274 x 240 MM	
	Insulated Ice Boxes	Capacity 25 Litrs Outer Dia: (LxBxH) : 385 x 320 x 330 MM	
	Insulated Ice Boxes	Capacity 50 Litrs Outer Dia: (LxBxH) :597 x 387 x 400 MM	
	Insulated Ice Boxes	Capacity 60 Litrs Outer Dia: (LxBxH) : 620 x 410 x 440 MM	
	Insulated Ice Boxes	Capacity 110 Litrs Outer Dia: (LxBxH) : 695 x 510 x 540 MM	
	Insulated Ice Boxes	Capacity 150 Litrs Outer Dia: (LxBxH) : 655 x 610 x 625 MM	
GN Pan			
	GN Pan 1/1	GN Pan 1/1 20 mm 530x325x20 mm Capacity 2.5 L	
		GN Pan 1/1 65 mm 530x325x65 mm Capacity 9.5 L	
		GN Pan 1/1 100 mm 530x325x100 mm Capacity 12.5 L	
		GN Pan 1/1 150 mm 530x325x150 mm Capacity 20 L	
		GN Pan 1/1 200 mm 530x325x200 mm Capacity 28 L	













	GN Lid 1/1	GN Lid 1/1 530x325 mm
	GN Pan 1/2	GN Pan 1/2 65 mm 325x265x65 mm Capacity 4 L
		GN Pan 1/2 100 mm 325x265x100 mm Capacity 6 L
		GN Pan 1/2 150 mm 325x265x150 mm Capacity 9.2 L
		GN Pan 1/2 200 mm 325x265x200 mm Capacity 12 L
	GN Lid 1/2	GN Lid 1/2 325x265 mm
	GN Pan 1/3	GN Pan 1/3 65 mm 325x176x65 mm Capacity 2.4 L
		GN Pan 1/3 100 mm 325x176x100 mm Capacity 3.5 L
		GN Pan 1/3 150 mm 325x176x150 mm Capacity 5.5 L
		GN Pan 1/3 200 mm 325x176x200 mm Capacity 7.5 L
	GN Lid 1/3	GN Lid 1/3 325x176 mm
	GN Pan 1/4	GN Pan 1/4 65 mm 265x162x65 mm Capacity 1.7 L
		GN Pan 1/4 100 mm 265x162x100 mm Capacity 2.5 L
		GN Pan 1/4 150 mm 265x162x150 mm Capacity 4 L
		GN Pan 1/4 200 mm 265x162x200 mm Capacity 5.2 L
	GN Lid 1/4	GN Lid 1/4 265x162 mm
	GN Pan 1/6	GN Pan 1/6 65 mm 176x162x65 mm Capacity 1 L
		GN Pan 1/6 100 mm 176x162x100 mm Capacity 1.5 L
		GN Pan 1/6 150 mm 176x162x150 mm Capacity 2.2 L
		GN Pan 1/6 200 mm 176x162x200 mm Capacity 3.2 L
	GN Lid 1/6	GN Lid 1/6 176x162 mm
	GN Pan 1/9	GN Pan 1/9 65 mm 176x108x65 mm Capacity 0.5 L
		GN Pan 1/9 100 mm 176x108x100 mm Capacity 0.7 L
		GN Pan 1/9 150 mm 176x108x150 mm Capacity 1 L
	GN Lid 1/9	GN Lid 1/9 176x108 mm
	GN Pan 2/1	GN Pan 2/1 65mm 650X530X65 mm Capacity 18.4 L
		GN Pan 2/1 100mm 650X530X100 mm Capacity 28.9 L
	GN Lid 2/1	GN Pan 2/1 100mm 650X530X100 mm Capacity 28.9 L
	GN Pan 2/3	GN Pan 2/3 65mm 650X530X65 mm Capacity 18.4 L
		GN Pan 2/3 100mm 650X530X100 mm Capacity 28.9 L
		GN Pan 2/3 150mm 650X530X150 mm Capacity 18.4 L
		GN Pan 2/3 200mm 650X530X200 mm Capacity 28.9 L
	GN Lid 2/3	GN LID 2/3 650X530 mm
PERFORATED GN PAN		
	GN Perforated Pan 1/1	PERFORATED GN PAN 1/1 x 65mm 530x325x65 mm
		PERFORATED GN PAN 1/1 x 100mm 530x325x100 mm
		PERFORATED GN PAN 1/1 x 150mm 530x325x150 mm
		PERFORATED GN PAN 1/1 x 200mm 530x325x200 mm
	GN Perforated Pan 1/2	PERFORATED GN PAN 1/2 x 65mm 325x265x65 mm
		PERFORATED GN PAN 1/2 x 100mm 325x265x65 mm
		PERFORATED GN PAN 1/2 x 150mm 325x265x150 mm
		PERFORATED GN PAN 1/2 x 200mm 325x265x200 mm
	GN Perforated Pan 2/3	GN Pan 2/3 65mm 650X530X65 mm Capacity 18.4 L
		GN Pan 2/3 100mm 650X530X100 mm Capacity 28.9 L
	GN Lid 1/1 SILICON COVERS	GN Lid 1/2 325x265 mm


























	GN Lid 1/2 SILICON COVERS	GN Lid 1/2 325x265 mm		
	GN Lid 1/3 SILICON COVERS	GN Pan 1/3 65 mm 325x176		
	GN Pan 2/4	GN PAN 2/4 65 mm 530x162x65 mm Capacity 6.5 L		
		GN PAN 2/4 100 mm 530x162x100 mm Capacity 6 L		
		GN PAN 2/4 150 mm 530x162x150 mm Capacity 9 L		
	GN Lid 2/4	GN LID 2/4 530x162 mm		
	ICE CREAM PAN	ICE CREAM PAN 200 mm 210X200X200 mm		
	ICE CREAM PAN	ICE CREAM PAN 150 mm 210X200X150 mm		
	ICE CREAM PAN LID			
	GILLETTO PAN 100MM	ICE CREAM PAN 100 mm 360X165X100 mm		
	GILLETTO PAN 120MM	ICE CREAM PAN 120 mm 360X165X120 mm		
	GILLETTO PAN 150MM	ICE CREAM PAN 150 mm 360X165X150 mm		
14/4 GN pans				
	GN Pan 1/1	GN Pan 1/1 20 mm 530x325x20 mm Capacity 2.5 L		
		GN Pan 1/1 65 mm 530x325x65 mm Capacity 9.5 L		
		GN Pan 1/1 100 mm 530x325x100 mm Capacity 12.5 L		
		GN Pan 1/1 150 mm 530x325x150 mm Capacity 20 L		
		GN Pan 1/1 200 mm 530x325x200 mm Capacity 28 L		
	GN Lid 1/1	GN Lid 1/1 530x325 mm		
	GN Pan 1/2	GN Pan 1/2 65 mm 325x265x65 mm Capacity 4 L		
		GN Pan 1/2 100 mm 325x265x100 mm Capacity 6 L		
		GN Pan 1/2 150 mm 325x265x150 mm Capacity 9.2 L		
		GN Pan 1/2 200 mm 325x265x200 mm Capacity 12 L		
	GN Lid 1/2	GN Lid 1/2 325x265 mm		
	GN Pan 1/3	GN Pan 1/3 65 mm 325x176x65 mm Capacity 2.4 L		
		GN Pan 1/3 100 mm 325x176x100 mm Capacity 3.5 L		
		GN Pan 1/3 150 mm 325x176x150 mm Capacity 5.5 L		
		GN Pan 1/3 200 mm 325x176x200 mm Capacity 7.5 L		
	GN Lid 1/3	GN Lid 1/3 325x176 mm		
	GN Pan 1/4	GN Pan 1/4 65 mm 265x162x65 mm Capacity 1.7 L		
		GN Pan 1/4 100 mm 265x162x100 mm Capacity 2.5 L		
		GN Pan 1/4 150 mm 265x162x150 mm Capacity 4 L		
		GN Pan 1/4 200 mm 265x162x200 mm Capacity 5.2 L		
	GN Lid 1/4	GN Lid 1/4 265x162 mm		
	GN Pan 1/6	GN Pan 1/6 65 mm 176x162x65 mm Capacity 1 L		
		GN Pan 1/6 100 mm 176x162x100 mm Capacity 1.5 L		
		GN Pan 1/6 150 mm 176x162x150 mm Capacity 2.2 L		
		GN Pan 1/6 200 mm 176x162x200 mm Capacity 3.2 L		
	GN Lid 1/6	GN Lid 1/6 176x162 mm		
	GN Pan 1/9	GN Pan 1/9 65 mm 176x108x65 mm Capacity 0.5 L		
		GN Pan 1/9 100 mm 176x108x100 mm Capacity 0.7 L		
		GN Pan 1/9 150 mm 176x108x150 mm Capacity 1 L		
	GN Lid 1/9	GN Lid 1/9 176x108 mm		
	GN Pan 2/3	GN Pan 2/3 20mm 650X530X20 mm Capacity 18.4 L		
		GN Pan 2/3 40mm 650X530X40 mm Capacity 18.4 L		










	GN Pan 2/3	GN Pan 2/3 65mm 650X530X65 mm Capacity 18.4 L	
		GN Pan 2/3 100mm 650X530X100 mm Capacity 28.9 L	
		GN Pan 2/3 150mm 650X530X150 mm Capacity 18.4 L	
		GN Pan 2/3 200mm 650X530X200 mm Capacity 28.9 L	
	GN Lid 2/3	GN LID 2/3 650X530 mm	
PERFORATED GN PAN			
	GN Perforated Pan 1/1	PERFORATED GN PAN 1/1 x 65mm 530x325x65 mm	
		PERFORATED GN PAN 1/1 x 100mm 530x325x100 mm	
		PERFORATED GN PAN 1/1 x 150mm 530x325x150 mm	
		PERFORATED GN PAN 1/1 x 200mm 530x325x200 mm	
	GN Perforated Pan 1/2	PERFORATED GN PAN 1/2 x 65mm 325x265x65 mm	
		PERFORATED GN PAN 1/2 x 100mm 325x265x65 mm	
		PERFORATED GN PAN 1/2 x 150mm 325x265x150 mm	
		PERFORATED GN PAN 1/2 x 200mm 325x265x200 mm	
	GN Pan Perforated Pan 2/3	GN PAN 2/3 65 mm 354x325x65 mm Capacity 5,25 L	
		GN PAN 2/3 100 mm 354x325x100 mm Capacity 8 L	
	GN Lid 2/3	GN LID 2/3 354x325 mm	
	GN Lid 1/1 SILICON COVERS	GN Lid 1/2 325x265 mm	
	GN Lid 1/2 SILICON COVERS	GN Lid 1/2 325x265 mm	
	GN Lid 1/3 SILICON COVERS	GN Pan 1/3 65 mm 325x176	
	GN Pan 2/4	GN PAN 2/4 65 mm 530x162x65 mm Capacity 65. 4 L	
		GN PAN 2/4 100 mm 530x162x100 mm Capacity 6 L	
		GN PAN 2/4 150 mm 530x162x150 mm Capacity 9 L	
	GN Lid 2/4	GN LID 2/4 530x162 mm	
	ICE CREAM PAN	ICE CREAM PAN 200 mm 210X200X200 mm	
	ICE CREAM PAN	ICE CREAM PAN 150 mm 210X200X150 mm	
	ICE CREAM PAN LID		
	GILLETTO PAN 100MM	ICE CREAM PAN 100 mm 360X165X100 mm	
	GILLETTO PAN 120MM	ICE CREAM PAN 120 mm 360X165X120 mm	
	GILLETTO PAN 150MM	ICE CREAM PAN 150 mm 360X165X150 mm	
Fabrication			
	S.S Stove Single burner	Dim: 27" x 27" x 24"ht	
	SS RING BIG SINGAL BURNER COOKING RANGE BULK	SS SHEET 16 304 TOP SIDES COVER 20 Guage PIPES 50 x 50 SIZE 30 x 30 x 24	
	2 Burner Range	Size: 48 * 24 * 34 + 6	
	3 Burner Range	Dim: 72" x 30" x 32"ht	



	4 Burner Range	Dim: 32" x 32" x 32"ht	
	SS 6 Burner Range	Size : 45"x33"x48" Top: SS 16 SWG sheet. Inner Support Angle : MS 1 1/4 X 1/4 4 side covered : SS 20 SWG sheet. Leg : SS 16 SWG 1 1/2" Square pipe With Adjustable Nylon Boots. T- 35 Burner - 4Nos. High flame burner 2Nos. Cast iron grid -6Nos	
	Bain Marie 4 Rectangular 6 Container	Size: 72 x 26 x 34	
	SS Work Table With 1 OHS 3 Side cover	Size: 72 x 30 x 34 + 18	
	Biryani Warmer	Size: 30 x 30 x 24	
	Biryani Burner 3 Layers	Size: 30 x 30 x 24	
	TANDOORI OVEN MACHINE	Size : Length 24" X Width 24" X Height 37" Measurement In Inch. Material: Stainless Steel 202, Base Plate 2.5 mm, 5" Inch Wheel. Packing Material: Glass Wool Packing. Clay Pot Size : Mouth 14" inch, Stomach 20" inch, Height 32"inch. EXTRA COST GAS FITTING: Gas Burner : Model – 4 with MS Stand Gas Fitting : Stainless MCV Control, Black LPG HOSE 3/8*3/8, LPG Adapter NHP (Or) PUNYA Welding Type: Arc & Matt Finish	
	Single Sink	Size: 24 * 24 * 34 + 6	
	SS work table with sink(304 Grade) 72"x24"x34" SS TOP & Sink: 16SWG SS Sheet SS bottom Shelf : SS 20 SWG Sheet, legs:SS 1 1/2" Round pipe in 16SWG With Adjustable Nylon Boots	Size :72"x24"x34"	
	SS Full SINK UINT WASHIG	48x24x34+6	
	Pre Wash Sink Unit	1800*750*850+150	
	Chinee 3 Burner Range with water chamber	Dim: 72" x 30" x 32"ht	












	S.S Dosa tawa	60x28x34+6 GAS OPERATED	
	SS IDLY BOX COOKING STEMER WITH STAND	180 CAPACITY FOR IDLY 52"	
	SS MASALA TOLLEY 1 KEG CONTAINER 12	Dimensions: 24x30x34	
	SS POT RACK FOR VESSEL STORAGE THEER SHELF	Dimensions: 20x48x60	
	SS Working Table	Size: 5 x 3 x 2.9	
	BAIN MARIE COUNTER WITH 3 SIDES COVERED WITH 4 NOS 1/2 GN PANS PROVISION WITH BOTTOM SHELF WITH HEATING ELEMENT WITH ON/OFF SWITCH WITH THERMOSTAT WITH INDICATOR	Size: 700 X 650 X 850	
	<u>Baine Marie</u> :Service counter with 6 containers (5 Nos with Heater + 1 No Normal) of 25ltrs capacity fitted with 2KW heating coil	Dim: 84" x 28" x 34" + 12" Tray Slide	
	SS Trolley for Collection of used plates of Dim: 36" L x 24" x 40" H, with 1 shelves below.	Dim: 36" x 24" x 40"	
	SS Working table of size 4'L* 2'W of height 34" attached with 2' Width shelves below at 24" above FFL	Dim: 48" x 24" x 34"	
	SS Food Pick up trolley of dimension (36"Lx24"Wx40"H) with 1nos of shelves attached beneath	Dim: 36" x 24" x 34"	
	SS Raw item pick up trolley of dimension (36"Lx24"Wx40"H) with 1nos of shelves attached beneath	Dim: 36" x 24" x 34"	
	SS Vegetable rack of 6'Lx2'Wx6'H attached with 3 shelves at distance of 2'	Dim: 6' x 2' x 6' (Perforated)	







	SS Pot rack of 6'Lx2'Wx6'H attached with 3 shelves (round bars) at distance of 2'	Dim: 6' x 2' x 6' (Pipe)	
	SS plate rack of 6'Lx2'Wx6'H attached with 5 layers made of SS RHS (frames) & Round pipes (plates) of 304 gauge		
	Steam Double jacket Rice vessel capacity 20Kg		
	Steam Double jacket sambar vessel capacity 20Kg		
	Steam Double jacket Milk vessel (100Ltrs Capacity)		
	Coconut Scraper	Product Type : Coconut Scraper Material : Stainless Steel Motor : 1 HP Capacity : 50-100 Kgs/Hr Speed : 960 RPM Dimension (L x W x H) : 21 x 12 x 20 inch (53.34 x 30.48 x 50.8 cm) Weight : 26 Kgs (Approx.)	
	60 Ltrs Capacity Cooker		
	SS SPOON (2) STERILIZER ELECTRICAL OPERATED COIL KV	Dimensions: 18x18x20	
	SS Dining Table (Size:2300mmx450mmx750mm) Top:20SWG Sheet Legs: 1.25" SQR Tube:16 SWG Top Inner Frame Support 1" Square Tube 304 Grade	SS + MDS dining table	
	Hood 6 ft 1mm 304 SS	6ft	
	3 H.P Heavy Duty High Speed Centrifugal LL Blower Fan 6000 CFM 50 - 60mm Static Pressure Air Maximum Noise Level - 85 DBA Unit With Dynamic Balancing Impeller with Crompton Motor 1440 RPM	3HP	
	Blower fan/ 1440 To 2880 Rpm 3 Phase - 5 HP Centrifugal Air Blower	5 HP	












	Duct line for exhaust- indicative sq feet 250 -Cross section wise- extra running feet 35 ft (with bends considered)	MS	
Refrigeration Static			
	4 Door Vertical Chiller	Capacity : 1000 Litrs Size. (mm) : 1220 x 692 x 1887 Temp. : +0°C ~ +10°C Power : 0.29 kw, 220V	
	4 Door Vertical Freezer	Capacity : 1000 Litrs Size. (mm) : 1220 x 692 x 1887 Temp. : -18°C ~ -15°C Power : 0.30 kw, 220V	
	2 Door Vertical Chiller	Capacity : 500 Litrs Size. (mm) : 620 x 692 x 1887 Temp. : +0°C ~ +10°C Power : 0.16 kw, 220V	
	2 Door Vertical Freezer	Capacity : 500 Litrs Size. (mm) : 620 x 692 x 1887 Temp. : -18°C ~ -15°C Power : 0.17 kw, 220V	
	2 Door Under Counter Chiller	Capacity : 350 Litrs Size. (mm) : 1200 x 700 x 800 Temp. : +0°C ~ +10°C Power : 0.16 kw, 220V	
	2 Door Under Counter Chiller	Capacity : 450 Litrs Size. (mm) : 1500 x 700 x 800 Temp. : +0°C ~ +10°C Power : 0.16 kw, 220V	
	2 Door Under Counter Freezer	Capacity : 350 Litrs Size. (mm) : 1200x700x800 Temp. : -18°C ~ -12°C Power : 0.35 kw, 220V	
	3 Door Under Counter Chiller	Capacity : 550 Litrs Size. (mm) : 1800 x 700 x 800 Temp. : +0°C ~ +10°C Power : 0.16 kw, 220V	
	3 Door Under Counter Freezer	Capacity : 550 Litrs Size. (mm) : 1800x700x800 Temp. : -18°C ~ -12°C Power : 0.30 kw, 220V	
	Salad Counter - Two door Without GN Pan	Capacity : 5 x 1/6 GN Size. (mm) : 900 x 700 x 970 Temp. : +2°C ~ +8°C Power : 0.25 kw, 220V	
	Salad Counter - Three door Without GN Pan	Capacity : 6 x 1/4 GN Size. (mm) : 1365 x 700 x 970 Temp. : +2°C ~ +8°C Power : 0.3 kw, 220V	
	2 Door Back Bar Chiller	Capacity : 250 Litrs Size. (mm) : 920 x 515 x 905 Temp. : +2°C ~ +8°C Power : 0.16 kw, 220V	
	3 Door Back Bar Chiller	Capacity : 315 Litrs Size. (mm) : 1350 x 515 x 905 Temp. : +2°C ~ +8°C Power : 0.24 kw, 220V	
Refrigeration Ventilated			
	VENTILATED REFRIGERATED GN CABINET 4*HALF SOLID DOOR REFRIGERATOR	Capacity : 1200 Litrs Size. (mm) : 1350 x 845 x 2000 Temp. : -2~+8 Power : 0.39 kw, 220V	












	VENTILATED REFRIGERATED GN CABINET 4*HALF SOLID DOOR FREEZER	Capacity : 1200 Litrs Size. (mm) : 1200 x 740 x 1950 Temp. : -18~-22 Power : 0.73 kw, 220V	
	VENTILATED REFRIGERATED GN CABINET 2*HALF SOLID DOOR REFRIGERATOR	Capacity : 600 Litrs Size. (mm) : 680 x 845 x 2000 Temp. : -2°C ~ +8°C Power : 0.21 kw, 220V	
	VENTILATED REFRIGERATED GN CABINET 2*HALF SOLID DOOR FREEZER	Capacity : 600 Litrs Size. (mm) : 680 x 845 x 2000 Temp. : -18~-22 Power : 0.47 kw, 220V	
	VENTILATED REFRIGERATED GN COUNTER 2 DOOR REFRIGERATOR	Capacity : 325 Litrs Size. (mm) : 1360 x 700 x 860 Temp. : -2oC ~ +8oC Power : 0.22 kw, 220V	
	VENTILATED REFRIGERATED GN COUNTER 2 DOOR REFRIGERATOR	Capacity : 300 Litrs Size. (mm) : 1360 x 700 x 860 Temp. : -2oC ~ +8oC Power : 0.52 kw, 22V	
	VENTILATED REFRIGERATED GN COUNTER 3 DOOR REFRIGERATOR	Capacity : 500 Litrs Size. (mm) : 1795 x 700 x 860 Temp. : -2oC ~ +8oC Power : 0.52 kw, 22V	
	VENTILATED REFRIGERATED GN COUNTER 3 DOOR FREEZER	Capacity : 500 Litrs Size. (mm) : 1795 x 700 x 860 Temp. : -2oC ~ +8oC Power : 0.52 kw, 22V	
Electric Prover			
	16 Tray Common Electric Prover	Dimension: 690*480*1930mm Volts: 220/50Hz Power : 2.1KW Capacity : 16 Pans Production : 40Kg/Hr N/W:32Kg	
	16 Tray Luxurious Electric Prover	1) Dimension: 500*770*1980mm 2) Voltage: 220V/50Hz 3) Power: 2.35KW 4) N/G Weight:55/65 5) 16 Tray : 400*600mm 6) Full SS Inside & Outside 7) With Timer	
	32 Tray Luxurious Electric Prover	1) Dimension: 1020*770*1980mm 2) Voltage: 220V/50Hz 3) Power: 3.2KW 4) N/G Weight:110/125 5) Full SS Inside & Outside 6) 32 Tray : 400*600mm 7) With timer	
	14 Tray Gas/Diesel Rotary Oven	14 Tray Gas/Diesel Rotary Oven 120 Bread Capacity : 75Kg to 100kg/Per Day Dry Flour. Usage/Application : Bread, Rusk, Cookies, Bun Etc., Phase : Three Baking Capacity : 14 Trays Power Source : Diesel/ GAS	
	24 Tray Gas/Diesel Rotary Oven	24 Tray Gas/Diesel Rotary Oven 168 Bread Number of Trays : 24 Trays Number Of Deck : 1 Deck For Baking : Bread/Bun Operation Type : Automatic Power Source : Diesel/GAS Usage/Application : Bakery Capacity : 400 kg Door Type : Single Door Body Material : Stainless Steel Maximum Temperature : 400 Degree C Power Consumption (KW) : 1.2 KW Size/Dimension : Tray size -13"x18"	
RK Machinery			
	2 HP Deluxe Gravy Machine 1.5"	2HP (DELUXE) Gravy Machine, Size: 500 x 675 x 375mm, Chamber Size: 6 x 3 Capacity: 35 – 40Kg, Weight: 38Kg	














	Potato peeler (20kg capacity)	Capacity : 20 Kg, Motor : 1.5 HP (1440 RPM), SIZE (L*W*H) : 29X18X40, Weight : 74 kgs, Time Duration : 7 - 10 minutes	
	Dough Kneading Machine 25KG	Size: 1200 X 700 X 1050mm, 25KG. FLOUR MIXING MACHINE 1.5HP MOTOR (1440RPM), Weight: 135 kg	
	ONION CUTTING MACHINE (CHOPPER MACHINE)	Size: 500 X 375 X 525, CAPACITY P/H. - 30 - 40KG MOTOR - 1HP 960RPM SIZE, Net Weight: 27Kg	
	ROUND MODEL - HEAVY DUTY MIXER GRINDER 10 LTR	Size: 275 X 375 X 775 mm, CAPACITY 10 LTR (2HP) MIXER MACHINE (ROUND MODEL) MOTOR - 1HP 2880RPM, Weight: 37 kg (Approx.)	
	3 HP 2 in 1 Pulveriser (Deluxe)	3HP 2IN1 PULVERISER (DELUXE) Size: 625 x 925 x 325mm, Chamber Size: 10 x 5 Capacity: 20 – 25Kg, Weight: 55Kg	
Dish washer			
	Under Counter Glass Washer (Crate 350/350)	Size : 420 x 450 x 620 Washing Cap : 20 Basket/Hr. Tank Cap : 12 Ltrs. Boiling Tank Cap : 2.8 Ltrs. Crate Size : 350 x 350mm Water Pressure Require : 2 - 3 Bar. Programing Time : 180 Second Power : 3.24 kw, 220V	
	Under Counter Dish Washer (Crate 500/500)	Size : 600 x 600 x 820 Washing Cap : 600 Plate/Hr. Washing Tank Cap : 24 Ltrs. Crate Size : 500 x 500mm Water Pressure Require : 2 - 3 Bar. Programing Time : 180 Second Power : 4.93 kw, 440V	
WM500E CO	WASHMATIC HOOD TYPE DISHWASHER WITH DOSING PUMP RINSE INJECTOR 2 RACKS/https://youtube.com/shorts/ HrdK5XC0VcY	Brand: WASHMATIC Model: WM500ECO Dim: L (mm) 620 W (mm) 750 H (mm) 1500 Material Main Body: Stainless Steel Power 7.2 KW, Phase THREE Capacity: 60 Racks/Hr; Tank Capacity: 25 LTR Included Accessory 2 Racks 500x500mm, Inlet Pipe, Drain Pipe, Main Lead, User Manual https://youtu.be/brnDY67CZMY	
WM902	WASHMATIC CONVEYOR DISHWASHER WITH DRYER (WITH DETERGENT AND RINSE PUMPS 3 RACKS)	Brand: WASHMATIC Model: WM902 Installation Type Freestanding Model Name/Number WM 902 Capacity (Racks / Hr.) 90 Capacity (Racks / Hr.) 1620 Rack Dimension (mm): 500 x 500 Dimension 1800 x 750 x 1725 / 1920 mm Tank Capacity (Litres): 80 Power Supply: 410V / 3ØN Gross Weight (Kg): 235	
WM904	WASHMATIC RACK CONVEYOR DISHWASHER WITH DRYER (WITH DETERGENT AND RINSE PUMPS 3 RACKS)	Brand: WASHMATIC Model: WM904 Installation Type Freestanding Model Name/Number WM 904 Capacity (Racks / Hr.) 135 Capacity (Racks / Hr.) 2430 Rack Dimension (mm): 500 x 500 Dimension 2400x750x1725/1920mm Tank Capacity (Litres): 80 + 34 Power Supply: 410V / 3ØN Gross Weight (Kg): 295	


EX-1DP00-H	Pre-Rinse Unit	Pre-Rinse Unit: 8" Deck Mount Mixing Faucet, Ceramic Cartridges, Lever Handles, 44" Flexible Stainless Steel Hose, 1.42 GPM Spray Valve, In-Line Check Valves, 6" Wall Bracket & 1/2" NPT Female Inlets	
	SS Loading Table With Sink With Splash Back with Left to Right side loading With Cross Support	SIZE: 1100 X 700 X 850+150MM SINK SIZE- 450X450X300MM DEEP	
	SS UnLoading Table With Bottom Shelf with Right to Left Unloading With Splash Back	SIZE: 1100 X 700 X 850+150MM	
	Washmate Supreme (Liquid Detergent Concentrate) – 20 Litres	Description Washmate Plus liquid detergent concentrate 20 Litre Packing Recommended dose 3 ml per litre of tank water	
	Rinsemate Sparkle (Liquid Rinse Aid Concentrate) 20 Litres	Description - Specially formulated for commercial dishwasher application, Assists drying process. Concentrated solution available in 20 Ltrs cans. Recommended dosage 1ml per litre of water	
	Dishwasher Tablet 20gms	Tablet Size – 20 gms Each pack contains 3 Nos total pack of 60 no's	
CRATE / TRAY WASHERS WASHMATIC MAKE			
WM860	CRATE / TRAY WASHERS WASHMATIC MAKE	Brand: WASHMATIC Model: WM860 Crate Size – 400 mm Crates / Hr. – 600 Crates Gross Weight – 445 Kgs Wash Zone – 3 Power Supply – 410 / 3ØN Over all Dimension – 3800 x 850 x 1560 x 1920 mm	 Model: WM860
WM820	CRATE / TRAY WASHERS WASHMATIC MAKE	Brand: WASHMATIC Model: WM820 Crate Size – 400 mm Crates / Hr. – 200 Crates Gross Weight – 215 Kgs Wash Zone – 1 Power Supply – 410 / 3ØN Over all Dimension – 2000 x 850 x 1560 x 1920 mm	 Model: WM820
WM840	CRATE / TRAY WASHERS WASHMATIC MAKE// https://youtu.be/pCo8s0dhCBQ	Brand: WASHMATIC Model: WM840 Crate Size – 400 mm Crates / Hr. – 400 Crates Gross Weight – 325 Kgs Wash Zone – 2 Power Supply – 410 / 3ØN Over all Dimension – 2900 x 850 x 1725 x 1920 mm	 Model: WM840
WM880	CRATE / TRAY WASHERS WASHMATIC MAKE	Brand: WASHMATIC Model: WM880 Crate Size – 400 mm Crates / Hr. – 800 Crates Gross Weight – 560 Kgs Wash Zone – 4 Power Supply – 410 / 3ØN Over all Dimension – 4700 x 850 x 1725 x 1920 mm	 Model: WM880
Chapati Machine			
ACM 300	Automatic Chapati Making Machine 300 Per Hour https://youtube.com/shorts/2zKIX01W0zA	Prod. Capacity: 300 Roti Per Hour Electric Supply: 230V (Single Phase) Electrical Connection Load: 4 HP Electric Consumption: 1.5 HP Unit Per Hour Chapati Baking: Three Conveyer Advance System Gas Consumption: 1 Kg. Per Hour Size of Roti: 4" to 7", Weight of Chapati: 20 to 50 Gm Bearing: High Temp. Absorber Overall Dimensions: 85 (L) X 45 (W) X 65(H) CM Weight of Machine: 150 Kgs Frame: SS All Contact Parts and Cover: SS 304	





	<p>Automatic Chapati Making Machine 500 Per Hour</p>	<p>Prod. Capacity: 500 Roti Per Hour Electric Supply: 230V (Single Phase) Electrical Connection Load: 4 HP Electric Consumption: 1.2 Unit Per Hour Chapati Baking: Three Conveyer Advance System Gas Safety: Auto Cut Off Valve System Gas Consumption: 2.2 Kg. Per Hour Size of Roti: 4" to 8", Weight of Chapati: 20 to 70 Gm Thickness of Chapati: 0.6mm to 2mm Motor Make: Godrej, Gear Box Make: Elecon Electrical Parts: Schneider, Electrical Safety: Emergency Switch Bearing: High Temp. Absorve + Bearing Cover Overall Dimensions: 4.7'(L) X 2.2'(W) X 3.7'(H) Weight of Machine: 370 Kgs</p>	
	<p>Automatic Chapati Making Machine 1000 Per Hour</p>	<p>Prod. Capacity: 1000 Roti Per Hour Electric Supply: 230V (Single Phase) Electrical Connection Load: 4 HP Electric Consumption: 1.2 Unit Per Hour Chapati Baking: Three Conveyer Advance System Gas Safety: Auto Cut Off Valve System Gas Consumption: 2.2 Kg. Per Hour Size of Roti: 4" to 8" Weight of Chapati: 20 to 70 Gm Thickness of Chapati: 0.6mm to 2mm Motor Make: Godrej Gear Box Make: Elecon Electrical Parts: Schneider Electrical Safety: Emergency Switch Bearing: High Temp. Absorve + Bearing Cover Overall Dimensions: 5"(L)X2.5(W)X4.7(H) Weight of Machine: 370 Kgs</p>	
	<p>Dough Ball Machine</p>	<p>Prod. Capacity: 1000 Roti Per Hour Weight of Dough: 20 to 70 Gm Electric Supply: 230V (Single Phase) Motor Make: Godrej Gear Box Make: Elecon Electrical Parts: Schneider Electrical Safety: Emergency Stop Button Machine Size: 2'(L)X1'(W)X5'(H) Weight of Machine: 80 Kgs</p>	
	<p>Automatic Chapati Making Machine 2000 Per Hour https://youtube.com/shorts/2zKIX01W0zA</p>	<p>Prod. Capacity: 2000 Roti Per Hour Electric Supply: 230V (Single Phase) Electrical Connection Load: 6.5 HP Electric Consumption: 4 Unit Per Hour Chapati Baking: Three Layer Technology 360 Degree Gas Safety: Auto Cut Off Valve System Gas Consumption: 3.5 Kg. Per Hour Size of Roti: 4" to 8" Weight of Chapati: 20.50 Gm Thickness of Chapati: 0.6mm to 2mm Motor Make: Godrej Gear Box Make: Elecon Electrical Parts: Schneider Electrical Safety: Emergency Push Button Bearing: High Temp. Absorve + Bearing Cover Overall Dimensions: 5.2(L)X3.5(W)X4.5(H) Weight of Machine: 450 Kgs</p>	
	<p>Dough Ball Machine</p>	<p>Prod. Capacity: 2000 Roti Per Hour Weight of Dough: 20 to 70 Gm Electric Supply: 230V (Single Phase) Motor Make: Godrej Gear Box Make: Elecon Electrical Parts: Schneider Electrical Safety: Emergency Stop Button Machine Size: 2'(L)X1'(W)X5'(H) Weight of Machine: 100 Kgs</p>	
	<p>Chapathi Pressing Machine/ https://youtube.com/shorts/4x5Kl4ibSI?feature=share</p>	<p>Capacity: 1000PH Chapatis per hour Automation Grade: Automatic Model Name/Number: CP 1000PH Material: Mild Steel Design Type: Conveyer Type Thickness Of Chapatti: 2.0mm Size/Dimension: 2.6X1.5X2.5inch(LxWxH) Type: Electric, Machine Weight: 80 Kgs Voltage: 230V, Motor Power Hp: 2 HP Phase Single Phase: Chapati Size: 4inch(Diameter)</p>	




	Chapa Pressing Machine	<p>Capacity: 2000PH Chapatis per hour Automation Grade: Automatic Model Name/Number: CP 2000PH Material: Mild Steel Design Type: Conveyor Type Thickness Of Chapatti: 2.0mm Size/Dimension: 2.6X1.5X2.5inch(LxWxH) Type: Electric, Machine Weight: 120 Kgs Voltage: 230V, Motor Power Hp: 4 HP Phase Single Phase: Chapati Size: 4inch(Diameter)</p>	
Pre-Rinse Units			
EX-1DP00-H	Pre-Rinse Unit	Pre-Rinse Unit: 8" Deck Mount Mixing Faucet, Ceramic Cartridges, Lever Handles, 44" Flexible Stainless Steel Hose, 1.42 GPM Spray Valve, In-Line Check Valves, 6" Wall Bracket & 1/2" NPT Female Inlets	
ZPRFW-PF4	Faucet Wall Mounted	Zephyr Tawa Dosa Cleaning Faucet Wall Mounted With single Hole Including 8Ft Food Grade Hose	
ZPRFW2	Faucet Wall Mounted	Zephyr Pre-Rinse Faucet - Wall Mounted	
ZPRFD1	Faucet - Deck Mounted Standard	Zephyr Pre-Rinse Faucet - Deck Mounted Standard	
ZPR001	Pre-Rinse Sprayer Food grade hose 13mm*3mtr with end 3/4 size end fittings https://youtu.be/RxQhMYdHFxc	No-Screw Design for Spray Face avoids latent leaking due to corroded screw, Heavy-Duty SS, Brass and POM Blastic Plastic Construction, Built-in Water Sealing EPDM Washer, SS 304 Spring for long-life High-Pressure & Powerful jet Spray, Easy assembly, disassembly for maintenance max. Pressure up to 60 BAR. Finish Polished Chrome, Black	
ZWR1015 HD-PR	Hose Reel for hygienic washing	Auto Retractable Kitchen WashStation.Hose ID 10mm x 15 Mtr Hose Length with Heavy Duty Rinse Sprayer	
Veg Cutting Machine			
	ELECTRIC VEGETABLE CUTTING MACHINE DF2 (2mm) DF5 (5mm) DT4 (4mm) DT10 (10mm) PS10 (10x10x10mm)	Electrical: Connection: 220V / 50Hz 110V / 60Hz Output, Power: 750W Slice Thickness: 2~10mm, RPM Rotations: 300 RPM, Dimensions: 59 x 27 x 48, Net Weight: 28Kg, Gross Weight: 33Kg	
	VEGETABLE CUTTING MACHINE (REGULAR) WITH 8 BLADE // https://youtu.be/wj_G9O93hrc	DESCRIPTION: 1HP MOTOR VEG. CUTT. MACHINE, (REGULAR) WITH 8 BLADE, SIZE (L*W*H): 20*11*23, WEIGHT: 40, CAPACITY P/H.: 150-200KG	
	Veg cutting machine// https://youtu.be/jED0jDUqfM	for cutting slicing dicing and shredding root veg -350 kg/hour / - Cutting Size: Slice-5 mm, Cube-20 mm and Shredding-3 mm - MOC: Stainless steel - Power: 1 HP, 220 V	
	Automatic Veg cutting machine-conveyor// https://youtu.be/O3w208tND1g	Double Head/Cutting Capacity:500-700 kg/hr//With Leafy cutting and Root vegetables cutting sections/Suitable for Cutting Root and Leafy Vegetables/ Leafy section is provided With Two Variable Frequency Drives for Conveyor and Cutting Blade Speed/ Cutting size can adjusted from Control panel/ Root vegetables cutting section has 3 different set of blades for slicing ,Cubing ,Julienne shapes,/With protections provided/ Machine stops when the door is opened/ With Food grade conveyor belt/ Power: 2.2 KW, 220 V, 50 Hz/ MOC : Stainless steel/ Blade Make: Taiwan	
Compartment Tray			

LB-8877	5 COMPARTMENT Stainless Steel Multicolor TOKYO BUFFET LUNCH BOX	5 grid, Capacity 1280ML, 850ML + 150ML Item Dim: LxWxH 28.5 x 22.5 x 7 CM (Includes: Spoon, Fork, Chopsticks SS) IDEAL FOR HOSPITALS, CATERERS, RESORTS, SCHOOL AND COPORATE STAFFS)	
LB-8849	4 COMPARTMENT Stainless Steel Multicolor TOKYO BUFFET LUNCH BOX	4 grid, Capacity 1000ML, 850ML + 150ML Dim: LxWxH 25.4 x 18.2 x 6.5 CM (Includes: Spoon, Fork, Chopsticks SS) IDEAL FOR HOSPITALS, CATERERS, RESORTS, SCHOOL AND COPORATE STAFFS)	
LB-8859	3 COMPARTMENT Stainless Steel Multicolor TOKYO BUFFET LUNCH BOX	3 grid, Capacity 750ML, 850ML + 150ML Dim: LxWxH 25 x 18 x 6.5 CM (Includes: Spoon, Fork, Chopsticks SS) IDEAL FOR HOSPITALS, CATERERS, RESORTS, SCHOOL AND COPORATE STAFFS)	
LB-8879 Tako	2 COMPARTMENT Stainless Steel Multicolor TOKYO BUFFET LUNCH BOX	2 grid, Capacity 500ML, + 150ML Dimensions LxWxH 22.4 x 16 x 6.9 CM IDEAL FOR HOSPITALS, CATERERS, RESORTS, SCHOOL AND COPORATE STAFFS)	
	Steel on - Insulated Tiffin Box 4-Tiered stainless-Steel	4-Tiered SS Insulated Tiffin Box Carrier Outer Dimensions / H: 10cm x Dia 6cm Inner Carrier Dimensions / H: 7cm x Dia 4.5cm Papped Box Dia: 4.5cm, Weight of the Container: 0.467 Capacity: 1720ML	
	Steel on - Insulated Tiffin Box 5-Tiered stainless-Steel	5-Tiered SS Insulated Tiffin Box Carrier Outer Dimensions / H: 10cm x Dia 6cm Inner Carrier Dimensions / H: 8cm x Dia 4.5cm Weight of the Container: 0.575 Capacity: 1800ML	
	06 COMPARTMENT PLATE HEAT RESISTANCE: -10 TO +75 DEGREE	Size: 10" x 14"	
	06 COMPARTMENT TRANSLUCENT LID	Size: 10" x 14"	
	03 COMPARTMENT PLATE HEAT RESISTANCE: -10 TO +75 DEGREE	Size: 10" x 8"	
	03 COMPARTMENT TRANSLUCENT LID	Size: 10" x 8"	
	04 COMPARTMENT PLATE HEAT RESISTANCE: -10 TO +75 DEGRE	SIZE: 10" x 12"	
	Polycarbonate lunch plates – 7 Compartments	07 COMPARTMENT PLATE HEAT RESISTANCE: -10 TO +75 DEGREE Size: 10" x 14"	
	Insulated Corolla Flask	250ml	
		350ml	
		550ml	
		750ml	
		1000ml	
		1500ml	
		2000ml	







	ELECTRIC TEA KETTLE 2LTR SCRALET		
	AIR FRESHENER	Chlorofluorocarbon & carcinogenic chemical free commercial Air freshener. Developed both Oil & Water based Air fresheners. Available in variety of modern blended aroma scents. Long lasting duration of purest aroma round the clock. ANTI-SMOKE for killing smoking / foul / Stinking / musty & Strong unpleasant disgusting odours without masking them \ with any other flowery aroma.	
	Anti Bacterial Air Sanitizer	Automatic Device is in the OFF Position Direct the device away from the face before switching it ON. When it is Switched ON, the device will automatically spray after 2 Sec.	
	HAND DRYER WHITE	LED PANEL- WHITE HAND DRYER 2 WAVES 1800W	
	Industrial Crates	64315 CC SW 650 X 450 X 315	
	Industrial Crates	64315 CC DW 650 X 450 X 315	
	Industrial Crates	Capacity 22 L Material Plastic Color Blue Shape Rectangular Outside Dimension 600 x 400 x 120 mm Inside Dimension 565 x 365 x 113 mm	
	Industrial Crates	Model : 43150 CC Capacity : 13 Ltrs OD : 400 (L)X 300(B) X 150 (H)Mm ID : 360(L)X 260(B)X 145(H)Mm	
	Industrial Crates	64085 TP 600 X 400 x 85	
	Industrial Crates	Model : 64225 SP Capacity : 45 Ltrs OD : 600 (L)X 400 (B) X 225 (H)Mm ID : 565 (L)X 365 (B)X 220 (H)Mm	
	Crate 500 x 325	Item Code: 53360 CH/CC Dimension: O.D: 500 x 325 x 360mm ID: 468 x 292 x 352mm Capacity: 47.00 Ltrs	
	LID 5300	Dimension: 500 X 325 X 21 MM	
	6400 Lid	600 X 400 Lid	
	4300 Lid	400 X 300 Lid	








	Ingredient Bin With Trolley	PC Ingredient Bin Size: 750 x 457 x 748 mm Capacity: 120 Ltr	
SP 1210	Pallet	Size: 1200 x 1000 x 125	
SP 1210	Pallet	Size: Length : 1200mm Width : 1000mm Height : 120mm STATIC : 3000 kg. Unified Load DYNAMIC: Up to 1000 kg. Unified Load RACKING : Not applicable	
	Plastic Pallet with puff insulation without steel reinforcement Plastic Pallet with puff insulation with steel reinforcement	Size: 1200 x 1000 x 160 mm Capacity : Static – 4000 kgs, Dynamic – 1000 kgs	
Other Equipment			
	Stainless Steel Popcorn Machine	Material: Stainless Steel Capacity: 80 Kg/hr Weight (kg): 20 Kilograms (kg) Automatic: Yes, Voltage: 220 Volt (v) Power: 1400 Watt (w) Dimension(L*W*H): 560 x 400 x 710 (mm)	
	ELECTRIC SOUP POT 10LTR BLACK	Capacity: 10 Ltr	
	ELECTRIC SOUP POT 10LTR SS WITH 3 PIN	Capacity: 10 Ltr	
	ELECTRIC MS ICE CREAM MACHINE	Capacity : 1000 Cones/Hr Type of Ice Cream Machine: Ice Cream Cone Making Machine Production Capacity : 10 Litre Frequency : 50 Mounting Position: STANDING Phase: 1 Power W: 2100 W Dimensions: 540X750X1320.MM	
	ELECTRIC ICE CREAM MACHINE COUNTER TOP	Type of Ice Cream Machine: Ice Cream Cone Making Machine Tank Capacity : 11 - 25 Litre, 20 Litre Phase: SINGLE PHASE	
Induction Equipment			
	Electric Incuction Stove - Flat	Dimensions (mm): 360*420*105 Power (W): 3500, Volts/V: 220	
	INDUCTION UNDER COUNTER 2.5 KW STEEL BODY (PUSH BUTTON)	POWER - 2500 W WEIGHT - 4 KGALL	
PA-CW-02	Chaffer Warmer	Buffet induction single zone Warranty on manufacturing defects 6months Watt 2.5 kw digital controller 220v ac Size: 315 x 315 x 70 mm with ss housing / heavy duty adjustable power	












	KGINDUCTION 3.5 KW WOKWITH KADAI STEEL BODY (KNOB HANDLE)	POWER -3500 W SIZE - 450x350x150 mm VOLTAGE - 220V~, 50 Hz WEIGHT - 6.5 KG	
	INDUCTION 5 KW WOK WITHKADAI STEELBODY (KNOBHANDLE)	POWER - 5000 W SIZE - 500x380x184 mm VOLTAGE - 220V~, 50 Hz WEIGHT - 6.5 KGRS	
	INDUCTION APPAM KADAI	POWER - 1.5KW VOLTAGE - 220V~, 50 Hz MIN TEMP: 45oC MIX TEMP: 240oC	
Hospital Cart			
HHC30S	Hospital Cart	<p>Dimensions (L W H): 550 x 710 x 1400 mm Temperature +30 to +90°C Power 230v / 50hz / 1 ph / 0.900kW Heating & Control Uniform, low density thermal heating, precise microprocessor control Heatup Time 20 minutes approx Capacity 30 Trays (Tray Size – 335 x 265 mm) Door Single, fully openable Handle & Lock Heavy duty edge mounted, magnetic latch, cylinder lock Castors 100mm dia, 2 lock, noise free Features All removable, adjustable, easily cleanable shelves Features GN Pans and Trays are interchangeable without tools Body Design Double walled, fully insulated – exterior and interior body with thermal separation Protection Type IP 54 Material AISI 304 – Brush 18/10, PE Accessories 2 universal SS trays included Optional Extras - Various depths of 1/1 GN Pans - Universal SS Wire Trays</p>	
HHC60D	Hospital Cart/ https://youtube.com/shorts/EhkRjcvvPZs	<p>Dimensions (L W H): 1070 x 710 x 1400 mm Temperature +30 to +90°C Power 230v / 50hz / 1 ph / 1.2kW Heating & Control Uniform, low density thermal heating, precise microprocessor control Heatup Time 25 minutes approx Capacity 60 Trays (Tray Size – 335 x 265 mm) Door Double, fully openable Handle & Lock Heavy duty edge mounted, magnetic latch, cylinder lock Castors 100mm dia, 2 lock, noise free Features All removable, adjustable, easily cleanable shelves Features GN Pans and Trays are interchangeable without tools Body Design Double walled, fully insulated – exterior and interior body with thermal separation Protection Type IP 54 Material AISI 304 – Brush 18/10, PE Accessories 4 universal SS trays included Optional Extras - Various depths of 1/1 GN Pans - Universal SS Wire Trays</p>	
SS Dustbin			
MBPLS81 2	PLASTEEL SWING BIN SS 202 (0.5mm) 9 Ltr Swing lid cover with LLDPE plastic shell	Overall Size: DIA 8” X H12” Litre: 9 Ltrs	
MBSB812 B	SS SWING BIN SS 202 (0.5 mm) 9Ltr Swing bin with matt polished.	Overall Size: DIA 8” X H12” Litre: 9 Ltrs	









MBPP813	SS PEDAL BIN WITH BUCKET SS 202 (0.5 mm) 7Ltr Swing bin with matt polished.	Overall Size: DIA 8" x H13" Litre: 7 Ltrs	
MBSB122 8B	SS SWING BIN SS 202 (0.5 mm) 50Ltr Swing bin with matt polished.	Overall Size: DIA12" x H28" Litre: 50 Ltrs	
	240L Wheeled Garbage Bin	Size 580 x 730 x 1080 mm Capacity 240 Litres Color Green	
	120L Wheeled Waste Bin	Capacity 120 Liter Size 480x550x940 Usage/Application Commercial Structure Open Top	
	90L Wheeled Garbage Dustbin	Size 470 x 550 x 658 mm Usage/Application Hospitals Color Orange Material Plastic	
	Twin Dustbin 10 Liter	W 31 x D 30 x H 41 (cm) Weight (Kg) 1.67	
Knife			
1135.1	Standard Knife	188mm	
CS-401	Carving Knife 4 Pcs		
1149.1	Carving Knife 5 inch	5 inch	
1172.1	Carving Knife		
1156.1	Chef Knife		
1157.1	Utility Knife		




















1182.3	Bread Knife		
1192.1	Chef Knife Deluxe		
1177.1	Chef Knife		
CL-4164.1/G	Cleaver Knife		
CL-1167.1/z	Cleaver Knife		
GR-31C/G	Slicer		
GR-21C/B	Grater Fine Edge		
Milk Can			
	20 L Plastic Milk Can	Capacity: 20 L	
	40 L Plastic Milk Can	Capacity: 40 L	
	50 L Plastic Milk Can	Capacity: 50 L	
	MILK CAN- 22 G (22 Gauge)	CAPACITY: 3 Ltr	
	MILK CAN- 22 G (22 Gauge)	CAPACITY: 5 Ltr	
	MILK CAN- 22 G (22 Gauge)	CAPACITY: 7.5 Ltr	
	MILK CAN- 22 G (22 Gauge)	CAPACITY: 10 Ltr	
	MILK CAN- 22 G (22 Gauge)	CAPACITY: 15 Ltr	
	MILK CAN- 22 G (22 Gauge)	CAPACITY: 20 Ltr	
	MILK CAN- 22 G (22 Gauge)	CAPACITY: 25 Ltr	
	MILK CAN- 18 G (18 Gauge)	CAPACITY: 30 Ltr	
	MILK CAN- 18 G (18 Gauge)	CAPACITY: 40 Ltr	
	MILK CAN- 18 G (18 Gauge)	CAPACITY: 50 Ltr	
	MILK CAN- (Aisi 304) For Dairy	CAPACITY: 20 Ltr	
	MILK CAN- (Aisi 304) For Dairy	CAPACITY: 30 Ltr	
	MILK CAN- (Aisi 304) For Dairy	CAPACITY: 40 Ltr	
Scan Box// https://www.youtube.com/watch?v=HEkJMaZmDgg			




















<p>TESHF14-CM-INDIA- Trayline</p>	<p>CM-India Hospital Tray (Single door) (HOT) Euronorm India Tray-Line (CM)- SINGLE Door X 14 levels X 1/1EuroNorm trays 370X530mm CM unit that can take 2 X Compartment Tray + Cover W360XL260XH65mm per level (total 28 compartment trays)-Note: Recommended tray: Cambro /BLUECHIP 6-Compartment Tray Code: 10416DCW+10416DCWC-</p>	<p>(Recommended patient tray: GN size tray size 530x325 mm: Ref: 3253) Duo Banquetline HOT & AMBIENT</p>	
<p>198245-1</p>	<p>TRAY-LINE - Hospital - 20-tray trolley. A20 + H10 (NEUTRAL (Cool) section with 20 trays and cooled by EUTECTIC PLATES placed on top of the unit after being frozen for 6 hours used to keep cold items cool + HOT section with 10 levels for plated hot food. The unit comes with 10 X Stainless Steel Grids (Neutral Section) + 10 Aluminum Shelves (Hot Section). The unit includes a foldable service table. (GN size Patient trays for the Ambien/ cooled section are not included in the unit)</p>	<p>(Recommended patient tray: GN size tray size 530x325 mm: Ref: 3253) Duo Banquetline HOT & AMBIENT</p>	
<p>Option 2</p>	<p>Ergo Line Single Door (1/1GN per level - Single Door) - HF12 (HOT - Convection Fan Heating)- (ExP)- (Old Codes: 111211-9)</p>	<p>https://www.scanbox.se/en/product/ergo-line-duo-active-cooling-hot-12-12</p>	
<p>ELSHS08</p>	<p>Ergo Line Single Door (1/1GN per level - Single Door) - HS08 (HOT - Static Heating) Single heating Static ExP (Old code-110811-7)</p>	<p>https://www.scanbox.se/en/product/ergo-line-hot-8</p>	
<p>ELSHS12</p>	<p>Ergo Line Single Door (1/1GN per level - Single Door) - HS12 (HOT - Static Heating) (Old Codes: 111211-9)</p>	<p>https://www.scanbox.se/en/product/ergo-line-hot-12</p>	
<p>ELSHS14</p>	<p>Ergo Line Single Door (1/1GN per level - Single Door) - HS14 (HOT - Static Heating) (Old Codes: 111411-5)</p>	<p>https://www.scanbox.se/en/product/ergo-line-hot-14</p>	












ELSHF12	Ergo Line Single Door (1/1GN per level - Single Door) - HF12 (HOT - Convection Fan Heating) Old Codes: 111211-9	https://www.scanbox.se/en/product/ergo-line-hot-12	
ELSCC08	Ergo Line Single Door (1/1GN per level - Single Door) - CC08 (COLD - Compressor Cooling)	https://www.scanbox.se/en/product/ergo-line-c8	
ELSCC10	Ergo Line Single Door (1/1GN per level - Single Door) - CC10 (COLD - Compressor Cooling)	https://www.scanbox.se/en/product/ergo-line-ac10	
ELSCC12	Ergo Line Single Door (1/1GN per level - Single Door) - CC12 (COLD - Compressor Cooling)	https://www.scanbox.se/en/product/ergo-line-active-cooling-12	
ELCCS66	Ergo Line Combo - (ExP) (Old Codes: 172006-1) (1/1GN per level) - Combo Hot+Cold in the same trolley - CC06+HS06 (COLD - Compressor Cooling + HOT - Static Heating)	https://www.scanbox.se/en/product/ergo-line-combo-active-cooling-hot-6-6	
BLCCF66	Banquet Line Combo (2/1GN per level) - Hot+Cold in the same trolley - CC06+HF06 (COLD - Compressor Cooling + HOT - Convection Fan Heating) Exp- (Old Codes: 196210-1) // https://www.youtube.com/watch?v=Le1RnntgXi8&t=1s	https://www.scanbox.se/en/product/banquet-line-combo-active-cooling-hot-6-6	
Bakery Equipments			
	1 Deck/2 Tray Baking Oven - Electric Operated Without Steam & Stone	Size : 1260 x 850 x 570mm Chamber Size : 870 x 655 x 200mm Tray Size : 600 x 400mm Temp : 20 ~ 300°C Timer Control : Yes Material : SS Outer Body painted and Chamber made with Aluminium Plate. Power : 6.3 kw, 220V Weight : 78/88 Kgs	

	1 Deck/2 Tray Baking Oven - Gas Operated Without Steam & Stone	<p>Size : 1340 x 880 x 650mm Tray Size : 600 x 400mm Chamber Size : 870 x 670 x 190mm Temp : 20~350°C Power : 0.1 kw, 220V Weight : 130/150 Kgs. Timer Controller available Material : Inside SS & Outer Side Aluminium Painted Body.</p>	
	Planetary Mixer - 10 Litres	<p>Capacity : 10 Ltrs. Size : 450 x 366 x 606mm Raw Flour : 3 Kgs. Power : 0.45 kw, 220V Mixing Speed : 110 x 360rpm Materials : SS Bowl & Cust Iron Body. Weight : 56/65 Kgs. Accessories : Hook, Whip, Beater</p>	
	Planetary Mixer - 20 Litres	<p>Capacity : 20 Ltrs. Size : 550 x 400 x 860mm Raw Flour : 6 Kgs. Power : 0.75 kw, 220V Materials : SS Bowl & Cust Iron Body. Weight : 80/95 Kgs. With Emergency Stop function. Accessories : Hook, Whip, Beater</p>	
	Planetary Mixer - 30 Litres	<p>Capacity : 30 Ltrs. Size : 550 x 400 x 960mm Raw Flour : 8 Kgs. Power : 0.95 kw, 220V Materials : SS Bowl & Cust Iron Body. Weight : 90/102 Kgs. With Emergency Stop function. Accessories : Hook, Whip, Beater</p>	
	Planetary Mixer - 40 Litres	<p>Capacity : 40 Ltrs. Size : 620 x 550 x 1050mm Raw Flour : 10 Kgs. Power : 1.5 kw, 440V Material : SS Bowl & Cust Iron Body. Weight : 150/170 Kgs. With Emergency Stop function. With Overload Protection Function. Accessories : Hook, Whip, Beater</p>	
	Spiral Mixer - 20 litres (Double Speed)	<p>Capacity : 20 Ltrs. Size : 675 x 400 x 825mm Raw Flour : 6 kgs. Power : 1.1 kw, 220V Weight : 92/112 Kgs Hook Mixing Speed : 250/125rpm Bowl Speed : 20/10rpm Material : SS Bowl Belt Transimission.</p>	
	Spiral Mixer - 40 litres (Double Speed)	<p>Capacity : 40 Ltrs. Size : 754 x 490 x 1055mm Raw Flour : 12 kgs. Power : 2.8 kw, 440V Weight : 133/153 Kgs Hook Mixing Speed : 250/125rpm Bowl Speed : 24/12rpm Weight : 59/76 Kgs. Material : SS Bowl Belt Transimission Two Timer Available</p>	
	Dough Keeping Machine	<p>40KG. FLOUR MIXING MACHINE 2HP THREE PHASE (1440RPM) SIZE (L*H*W): 50*42*25, WEIGHT: 158 TIME DURATION: 25-30 min.</p>	
	Dough Sheeter 630mm (Heavy Model)	<p>Size:1100x2950x1180mm Vol.:380V 50Hz / 0.75/KW N/G Weight: 225Kg 1. Max. Dough Capacity: 6.5 Kg/time 2. Resting Position: 780x1780mm 3. Working Position: 2950/1180mm 4. Belt Size 630*2400mm 5. Roller Adjustable Gap: 1-40mm</p>	
Ice Cube Machine & Bar Items			
	Ice Cube Machine - JE-25	<p>Capacity -25 Kgs/24 Hr. Size : 380 x 450 x 600 Ice Type : Cube, Storage Capacity : 7 Kgs. Water Pressure Require : 1.5 ~ 5.5 Bar Power : 0.17KW, 220V</p>	
	Ice-Cube Machine with Selft Contain Bin - JE-45	<p>Capacity -45 Kgs/24 Hr. Size : 550 x 656 x 880 Storage Capacity : 13 Kgs. Water Pressure Require : 1.5 ~ 5.5 Bar Condensing : Air Cooled Power : 0.36KW, 220V</p>	







	Ice-Cube Machine with Self Contain Bin	Capacity -60 Kgs/24 Hr. Size : 610 x 656 x 960 Storage Capacity : 22 Kgs. Condensing : Air Cooled Water Pressure Require : 1.5 ~ 5.5 Bar Ice Type : Cube, Power : 0.42KW, 220V	
	Ice-Cube Machine with Self Contain Bin	Capacity -100 Kgs/24 Hr. Size : 715 x 656 x 960 Storage Capacity : 28 Kgs. Water Pressure Require : 1.5 ~ 5.5 Bar Condensing : Air Cooled Ice Type : Cube Power : 0.7KW, 220V	
	BLENDERS	Hard Fighter Heavy duty Blender Rated Voltage : 220-240V, Rated Frequency : 50Hz/60Hz Rated Power : 1500W, Jar Capacity : 2.0L Jar Resistance : -40°C - 120°C, Max over-Current Protection : 10A Max over-heat Protection : 130°C	
	BAR BLENDERS	CAPACITY: 44 fl oz, 1310 ml MATERIAL: POLYCARBONATE CONTAINER, STAINLESS STEEL BLADES WEIGHT: 10.15 lb, HORSE POWER: ½ SWITCH ACTION: HIGH/LOW, ON/OFF/PULSE	
	BEER TOWER WITH ICE TUBE 3 LITER	Specification: Capacity : 3-4 L Size WxDxH : 18*18*84 Color: Transparent	
	Antiskid Tray	Dim: 16*	
	Antiskid Tray	Dim: 16*22	
	Cuttlery Holder	4 Compartment	
	Wood Tray Jack Stand	Dim: 650 x 460	
	Juice Dispensor	8 Ltrs	
	CUTTING BOARD	Size (18 x 24 x 1")	
	CUTTING BOARD	Size (18 x 24 x 2")	
	CUTTING BOARD	Size (24 x 36 x 1")	
	CUTTING BOARD	Size (24 x 36 x 2")	
SIB100	SHELF INGREDIENT BIN	Dimension (cm): 40x29.x22.8 Capacity: 10 L Colour: White	
SIB240	SHELF INGREDIENT BIN	Dimension (cm): 59.3x29.6x43.5 Capacity: 24 L Colour: White	
SIB470	SHELF INGREDIENT BIN	Dimension (cm): 59x48.5x43.8 Capacity: 47 L Colour: White	
IB01020	INGREDIENT BIN WITH WHEEL	Dimension (cm): 74.9x39.4x71.1 Capacity: 102 L Colour: White	
	Hot Water kettle	Prestige 1.5Ltr	


	Citrus Fruit Juicer	Fixable stand one Size. :210x210x310 Power :250W	
44974	Red Wine	395ml	
44743	Water (White Wine)	338ml	
42403	Juice Small	185ml	
44904	Martini	310ml	
44386	Margarita (S)	305ml	
42884	Whiskey	315ml	
42438	Hiball	215ml	
44929	Welcome drink	75ml	
52144	Shot	40ml	
	Bar Spoon(s)		
	Bar Spoon(B)		
	Shaker set two piece	COCKTAIL SHAKER REGULAR PIECE -ST.STEEL 540ml	
	PEG MEASURE INTERNATIONAL - ST.STEEL	25X50 ml	
	Shaker set three piece (cobbler)		
J8	Julep strainer	JULEP STRAINER REGULAR -ST.STEEL	
	Fine strainer		
	Mixing glass	BOSTON SHAKER GLASS 9X14.5 CM	
	hawthorne strainer	BAR STRAINER 4 PRONGS	

	Pe measure	MEASURING JUG 1 Ltr	
	Lemon Squeezer		
	Rimmer 3 tier	Bar Rimmer - ABS	
	Bar caddy		
	POURER	11 CM	
	ICE CUBE SCOOPER	24 CM	
	ICE CUBE SCOOPER	24 CM	
	Bar mats (counter) square		
	Bar mats (counter) rectangle		
	Melon Scooper		
	Peeler		
	Zester		
	Muddler	210 MM	
	Bar Blade	18 CM	
	Corck Screw opener		
	Butterfly opener		
	Bar Garnish caddy	Condiment Rack - 6	
	Q liners		
	Table Squeeze	12OZ	
	Squeeze bottle	16OZ	
	Store N pour	24OZ	
	Buffet Tag Holders	A5 Size	




	Tea pots-Glass		
	Pizza Spectoler		
	Ap spoon		
	Ap fork		
	Soup spoon		
	Ap knife		
	Sreak knife		
	Tea spoon		
	Dessart spoon		
	Dispensers	SS Soup Tureen-10 Ltrs	
	Dispensers	Soup Tureen (MS Black)-10Ltrs	
	Condement Dispenser 4 Pts W/Lid(N/M)	30 X 15 CM	
	Condiment Dispenser With Lid 6 Pints(N/M)	45 X 15 CM	
Waste Management System			
SE-501	ORGANIC WASTE CONVERTER	<p>Input Capacity: 50 Kg per cycle / batch Average Reduction Rate: 83 – 90% Processing time: 12 -14 hours Power Requirement: 3 phase, 50Hz, 415V Power consumption: 2.8 Kw Dimension: (L*W*H in mm): 1150*900*950 Weight: 300 Kg, Tank Volume: 3 Cu.Feet Material Durable stainless steel (SS-304)</p> <p>Safety Feature: The internal impeller automatically stops when the hopper door is opened</p> <p>Odour Treatment: Integrated deodorisation and foul odour control Installation: No need for special installation or exhaust ventilation Treatable Items: Food waste and all compostable disposables Untreatable Items: Metal waste, plastic, glass, petrochemicals.. Automation Controls: 7" touch screen, Fully automatic PLC Controlled (Touch screen for SE 1001 and above)</p> <p>Warranty: 1 year manufacturers Standard warranty</p>	
SE-1001	ORGANIC WASTE CONVERTER	<p>Input Capacity: 100 Kg per cycle / batch Average Reduction Rate: 83 – 90% Processing time: 14 -16 hours Power Requirement: 3 phase, 50Hz, 415V Power consumption: 4 Kw Dimension: (L*W*H in mm): 1200*1020*1145 Weight: 510 Kg, Tank Volume: 5 Cu.Feet Material Durable stainless steel (SS-304)</p>	
SE-2501	ORGANIC WASTE CONVERTER	<p>Input Capacity: 200 Kg per cycle / batch Average Reduction Rate: 83 – 90% Processing time: 15 -18 hours Power Requirement: 3 phase, 50Hz, 415V Power consumption: 6 Kw Dimension: (L*W*H in mm): 1475*1190*1170 Weight: 650 Kg, Tank Volume: 9 Cu.Feet Material Durable stainless steel (SS-304)</p>	
SE-3501	ORGANIC WASTE CONVERTER	<p>Input Capacity: 350 Kg per cycle / batch Average Reduction Rate: 83 – 90% Processing time: 15 -18 hours Power Requirement: 3 phase, 50Hz, 415V Power consumption: 8 Kw Dimension: (L*W*H in mm): 1475*1190*1170 Weight: 650 Kg, Tank Volume: 9 Cu.Feet Material Durable stainless steel (SS-304)</p>	
SE-5001	ORGANIC WASTE CONVERTER	<p>Input Capacity: 500 Kg per cycle / batch Average Reduction Rate: 83 – 90% Processing time: 18 -22 hours Power Requirement: 3 phase, 50Hz, 415V Power consumption: 9 Kw Dimension: (L*W*H in mm): 2345*1400*1450 Weight: 1100 Kg, Tank Volume: 21 Cu.Feet Material Durable stainless steel (SS-304)</p>	

SE-1H	ORGANIC WASTE CONVERTER	<p>Input Capacity: 1000 Kg per cycle / batch Average Reduction Rate: 83 – 90% Processing time: 24 -30 hours Power Requirement: 3 phase, 50Hz, 415V Power consumption: 12 Kw Dimension: (L*W*H in mm): 3100*1675*1850 Weight: 2100 Kg, Tank Volume: 41 Cu.Feet Material Durable stainless steel (SS-304)</p>	
SS Hot Pot			
	SS HOT POT HOT 'N' COLD	CAPACITY: 2500ML	 
	SS HOT POT HOT 'N' COLD	CAPACITY: 5000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 7500ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 10000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 15000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 20000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 25000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 30000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 40000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 50000ML	
	SS HOT POT HOT 'N' COLD	CAPACITY: 60000ML	
	Water Filter	CAPACITY: 18 Ltr 2 Candles	
	Water Filter	CAPACITY: 24 Ltr 3 Candles	
	Water Filter	CAPACITY: 34 Ltr 4 Candles	
	Water Filter	CAPACITY: 44 Ltr 4 Candles	
	Stock Pot	Mini (1.5 Ltrs)	
	Stock Pot	Smalli (3 Ltrs)	
	Stock Pot	Medium (5 Ltrs)	
	Stock Pot	Big (8 Ltrs)	
	Hot Pot Carriers	CAPACITY: 2500 x 4	
	Hot Pot Carriers	CAPACITY: 2500 x 5	
	Hot Pot Carriers	CAPACITY: 2500 x 6	
	Hot Pot Carriers	CAPACITY: 5000 x 3	
	Hot Pot Carriers	CAPACITY: 5000 x 4	
	Hot Pot Carriers	CAPACITY: 5000 x 5	
	Hot Pot Carriers	CAPACITY: 5000 x 6	
	Hot Pot Carriers	CAPACITY: 7500 x 3	
	Hot Pot Carriers	CAPACITY: 7500 x 4	
	Hot Pot Carriers	CAPACITY: 7500 x 5	
	Tea Can (PUF)	CAPACITY: 2.5 Ltr	
	Tea Can (PUF)	CAPACITY: 5 Ltr	
	Tea Can (PUF)	CAPACITY: 7.5 Ltr	


	Tea Can (PUF)	CAPACITY: 10 Ltr	
	Tea Can (PUF)	CAPACITY: 15 Ltr	
	Tea Can (PUF)	CAPACITY: 20 Ltr	
	Tea Can (PUF)	CAPACITY: 25 Ltr	
	Tea Can (PUF)	CAPACITY: 30 Ltr	
	Tea Can (PUF)	CAPACITY: 40 Ltr	
	Tea Can (PUF)	CAPACITY: 50 Ltr	
	Sleek Tea Can	CAPACITY: 5 Ltr	
	Sleek Tea Can	CAPACITY: 10 Ltr	
	Hot Tiffen (SS 304)	CAPACITY: 13 Ltr - with 6 Containers	
	Hot Tiffen (SS 304)	CAPACITY: 10 Ltr - with 5 Containers	
	Idly Cooker (W.Plates)	Big (6 Plates)	
	Idly Cooker (W.Plates)	Small (4 Plates)	
	SS BUCKETS (202 Gauge)	Height: 7" Weight: 700 gms	
	SS BUCKETS (202 Gauge)	Height: 8" Weight: 800 gms	
	SS BUCKETS (202 Gauge)	Height: 9" Weight: 950 gms	
	SS BUCKETS (202 Gauge)	Height: 10" Weight: 1.050 Kg	
	SS BUCKETS (304 Gauge)	Height: 7" Weight: 700 gms	
	SS BUCKETS (304 Gauge)	Height: 8" Weight: 800 gms	
	SS BUCKETS (304 Gauge)	Height: 9" Weight: 950 gms	
	SS BUCKETS (304 Gauge)	Height: 10" Weight: 1.050 Kg	
Home Water Purifier Normal Water			
	CABINET	Stainless Steel SS304 Body & Storage Tank Capacity — 8Ltrs Heavy Duty Faucet	
	RO 10S	Inline Filters — Sediment, Pre-Carbon& Post Carbon. Membrane, Booster Pump, Solenoid Valve 24DC, SMPS, Storage Capacity — 8Ltrs, Heavy Duty Faucet	
	RO+UV 10S	Inline Filters — Sediment, Pre-Carbon& Post Carbon. Membrane, Booster Pump, Solenoid Valve 24DC, SMPS, Storage Capacity — 8Ltrs, Heavy Duty Faucet & UV Purifier	
Water Purifier Normal & Hot			







	CABINET NH	Stainless Steel 55304 Body & Storage Tank Capacity — Normal 5Ltrs & Hot 2Ltrs, SS Heater Coil, Thermostat & Thermal Cutoff, Heavy Duty Faucet	
	RO 10S NH	Inline Filters — Sediment, Pre-Carbon& Post Carbon. Membrane, Booster Pump, Solenoid Valve 24DC, SMPS, Storage Capacity — Normal 5Ltrs & Hot 2Ltrs, SS Heater Coil, Thermostat & Thermal Cutoff, Heavy Duty Faucet	
	RO+UV 10S	Inline Filters — Sediment, Pre-Carbon& Post Carbon. Membrane, Booster Pump, Solenoid Valve 24DC, SMPS, Storage Capacity — Normal 5Ltrs & Hot 2Ltrs, SS Heater Coil, Thermostat & Thermal Cutoff, Heavy Duty Faucet & UV Purifier	













Hot Food for the Buffet- Chaffing fuel












	Chaffing Dish Fuel with Wick	4Hrs per Piece Price: INR: 30/- 140 ML	
	Chaffing Dish Fuel with Wick	6Hrs per Piece Price: INR: 34/- 210 ML	
	Fuel Gel Regular	Capacity: 200 grams	
	Fuel Gel Regular	Capacity: 160 grams	
	Fuel Gel Regular Coated tin export quality	Capacity: 225grams	
	Fuel Gel Coated tin export quality	Capacity: 200 grams	





Idli Steamer

	Gas Rice/ Idli/Momos/ Potato Steamer- (w/o tray)- ELITE-GS24 HSN Code = 8419	<p>Size(mm) - 1500X700X1750 of Tray - 24 trays Doors - 2 (MIN) - 35 mins, Idli Trays TIME (MIN) - 50 mins, Plain Trays 50 mins, With hole Trays With hole Trays hole Trays hole Trays potato, peas, vegetable blanching, momos, pasta, chicken, meat fish etc</p> <p>No. of Idli (Pcs) - 480 Idlies, TIME Rice (kg) Input/ Output - 40/120, Potato (Kg) - 120-140, TIME (MIN) - Momos (Pcs) - 1920, TIME (MIN) - 15 mins, Noodle (Kg) - 120, TIME (MIN) - 35 mins, With Egg (Pcs) - 1680 , TIME (MIN) - 35 mins, With LPG Kg/Hr - 2.4 • Steam rice, • Compact design, uniform cooking, fuel efficient. • Professional customized burner. • Auto ignition with flame failure device. • Stainless steel inner and outer body. • Foamed with heat resistant polyurethane for heat preservation and insulation. • Inbuilt water tank, automatic floating ball water control system. • Progressive door lock • Excess steam outlet • Analog temperature meter • High temperature resistant silicone rubber door gasket. • Food quality consistency. No overcooking, burning..</p>	
--	--	--	---

	<p>Gas Rice/ Idli/Momos/ Potato Steamer- (w/o tray)- ELITE-GS12 HSN Code = 8419</p>	<p>Size(mm) - 750X700X1750 No. of Tray - 12 trays Door - 1 (MIN) - 35 mins, Idli Trays TIME (MIN) - 50 mins, Plain Trays mins, With hole Trays mins, With hole Trays With hole Trays With hole Trays With hole Trays</p> <p>Idli (Pcs) - 240 Idlies, TIME Rice (kg) Input/ Output - 20/60, Potato (Kg) - 60-70, TIME (MIN) - 50 Momos (Pcs) - 960, TIME (MIN) - 15 Noodle (Kg) - 60, TIME (MIN) - 35 mins, Egg (Pcs) - 840 , TIME (MIN) - 35 mins, LPG Kg/Hr - 1.2 • Steam rice, potato, peas, vegetable blanching, momos, pasta, chicken, meat fish etc.</p> <ul style="list-style-type: none"> • Compact design, uniform cooking, fuel efficient. • Professional customized burner. • Auto ignition with flame failure device. • Stainless steel inner and outer body. • Foamed with heat resistant polyurethane for heat preservation and insulation. <ul style="list-style-type: none"> • Inbuilt water tank, automatic floating ball water control system. <ul style="list-style-type: none"> • Progressive door lock • Excess steam outlet • Analog temperature meter • High temperature resistant silicone rubber door gasket. • Food quality consistency. No overcooking, burning.. 	
	<p>Gas Rice/ Idli/Momos/ Potato Steamer- (w/o tray)- ELITE-GS6 HSN Code = 8419</p>	<p>Size(mm) - 750X700X1200 No. of Tray - 6 trays No. of Door - 1 TIME (MIN) - 35 mins, Idli Trays 10/30, TIME (MIN) - 50 mins, Plain Trays (MIN) - 50 mins, With hole Trays 15 mins, With hole Trays With hole Trays With hole Trays With hole Trays</p> <p>Idli (Pcs) - 120 Idlies, Rice (kg) Input/ Output - Potato (Kg) - 30-35, TIME Momos (Pcs) - 480, TIME (MIN) - Noodle (Kg) - 30, TIME (MIN) - 35 mins, Egg (Pcs) - 420 , TIME (MIN) - 35 mins, LPG Kg/Hr - 1.2 • Steam rice, potato, peas, vegetable blanching, momos, pasta, chicken, meat fish etc.</p> <ul style="list-style-type: none"> • Compact design, uniform cooking, fuel efficient. • Professional customized burner. • Auto ignition with flame failure device. • Stainless steel inner and outer body. • Foamed with heat resistant polyurethane for heat preservation and insulation. <ul style="list-style-type: none"> • Inbuilt water tank, automatic floating ball water control system. <ul style="list-style-type: none"> • Progressive door lock • Excess steam outlet • Analog temperature meter • High temperature resistant silicone rubber door gasket. • Food quality consistency. No overcooking, burning.. 	
	<p>Electric Rice / Idli/Momos/Potato. Steamer - (w/o tray)- ELITE - ES12 HSN Code = 8419 // https://www.youtube.com/watch?v=wnM3lpvOJXo</p>	<p>Size(mm) - 750X700X1700 No. of Tray - 12 trays Door - 1 (MIN) - 20 mins, Idli Trays TIME (MIN) - 30 mins, Plain Trays mins, With hole Trays mins, With hole Trays With hole Trays With hole Trays With hole Trays</p> <p>Idli (Pcs) - 240 Idlies, TIME Rice (kg) Input/ Output - 19/58, Potato (Kg) - 60, TIME (MIN) - 30 Momos (Pcs) - 960, TIME (MIN) - 10 Noodle (Kg) - 48, TIME (MIN) - 20 mins, Egg (Pcs) - 840 , TIME (MIN) - 20 mins, Electric Load - 380 V / 12 Kw • Steam rice, potato, peas, vegetable blanching, momos, pasta, chicken, meat fish etc •</p> <ul style="list-style-type: none"> • Compact design, uniform cooking. • Stainless steel inner and outer body. • Foamed with heat resistant polyurethane for heat preservation and insulation. <ul style="list-style-type: none"> • Inbuilt water tank, automatic floating ball water control system. <ul style="list-style-type: none"> • Progressive door lock • Excess steam outlet • High temperature resistant silicone rubber door gasket • Food quality consistency. No overcooking, burning. • Prevent dry run. Auto power cut off and alarm alert in case water level drops below water sensor pin. 	
<p>SS 304 Idli trays/24 idlis tray HSN Code = 8419</p>		<p>RAY TYPE - SS 304 Idli trays, Tray Size - 595x395</p>	
<p>SS 201 - Plain tray HSN Code = 8419</p>		<p>TRAY TYPE - SS 201 Plain Tray, Tray Size - 595x395</p>	
<p>SS 201 - Perforated tray HSN Code = 8419</p>		<p>TRAY TYPE - SS SS 201 - Perforated tray, Tray Size - 595x395</p>	
<p>Hoshizaki Refrigeration Ventilated</p>			

HRW-77 MS4	2 Door Upright Chiller	Volume: 628 Liters Dimensions (with 90mm leg): 700 (W) x 818 (D) x 1990 (H) Power Supply: 230V AC / 50Hz Temperature Range: -2°C to 12°C Door / Shelf: 4 nos. of shelves	
HFW-77 MS4	2 Door Upright Freezer	Volume: 628 Liters Dimensions (with 90mm leg): 700 (W) x 818 (D) x 1990 (H) Power Supply: 230V AC / 50Hz Temperature Range: -7°C to -25°C Door / Shelf: 4 nos. of shelves	
HRW-147MS4	4 Door Upright Chiller	Volume: 1365 Liters Dimensions (with 90mm leg): 1400 (W) x 818 (D) x 1990 (H) Power Supply: 230V AC / 50Hz Temperature Range: -2°C to 12°C Door / Shelf: 8 nos. of shelves	
HFW-147MS4	4 Door Upright Freezer	Volume: 1365 Liters Dimensions (with 90mm leg): 1400 (W) x 818 (D) x 1990 (H) Power Supply: 230V AC / 50Hz Temperature Range: -2°C to 12°C Door / Shelf: 8 nos. of shelves	
Western Hard Top and Vertical Freezers			
NWHD12 5H	Deep Freezer	Gross Volume: 103 Liters Dimensions (mm): 555 (W) x 640 (D) x 880 (H) Net Volume: 96 Liters No. of Basket: 1 Temperature Range: Freezer application : <-17°C Cooler application : <10°C Insulation: 60mm Polyurethane Hard Top Double door	
D350H	Deep Freezer	Number of Basket 1 No. Insulation 60mm Polyurethane Internal Dimension In mm 930 W x 530 D x 680 H External Dimension In mm 1060 W x 695 D x 840 H Ice Cream Loading 90 kg Gross Volume 335 Litres Net Volume 320.0 Litres Gross Volume: 546 Liters	
NWHD52 5H-HC	Deep Freezer	Dimensions (mm): 1606 (W) x 695 (D) x 840 (H) Net Volume: 495 Liters No. of Basket: 2 Temperature Range: Freezer application : <-17°C Cooler application : <10°C Insulation: 60mm Polyurethane Gross Volume: 546 Liters	
F250GL25	Deep Freezer Glass Top	Dimensions (mm): 760 (W) x 695 (D) x 882 (H) Net Volume: 227 Liters No. of Basket: 1 Temperature Range: Freezer application : <-17°C Cooler application : <10°C Insulation: 60mm Polyurethane	
Model: EW400	Everest Stabilizer	Electronic Voltage Stabilizer Model: EW400 Capacity: 4KVA Frequency: 50Hz Input Volts: 185-270 Output Volts: 200-240	
SRC 280 HC-GL	Visi Cooler Non - Canopy Models	External Dims. (mm): 514 (W) x 549 (D) x 1515 (H) Internal Dims. (mm): 434 (W) x 454 (D) x 1100 (H) Gross Volume: 216 Liters No. of Shelves: 04	
SRC 500 HC-GL	Visi Cooler Non - Canopy Models	External Dims. (mm): 583 (W) x 695 (D) x 2060 (H) Internal Dims. (mm): 503 (W) x 552 (D) x 1634 (H) Gross Volume: 453 Liters No. of Shelves: 06	
SRC 1050GL	Visi Cooler Double Door Model	External Dims. (mm): 1025 (W) x 707 (D) x 2052 (H) Internal Dims. (mm): 945 (W) x 552 (D) x 1592 (H) Gross Volume: 807 Liters No. of Shelves: 10	
BKE Machine			

<p>Precision Vegetable Cutters https://youtube.com/shorts/rLhrlpTYO4w?feature=share</p>		<p>Machine RPM 750 Vegetable Output Capacity 700 to 1500 kg Per Hour Motor Capacity 2 HP. 3 Phase / Single Phase Voltage 220 to 240 volts, 1440 RPM Dimensions (L x B x H): 750 x 660 x 150 (mm) Machine Weight: 67 Kg Cutting Disc Capabilities: Slicing: 1 to 15mm, Strips: 4 x 4, 6 x 8 Grating: 1mm to 5mm, Dicing: 7 x 7, 10 x 10, 15 x 15, 20 x 20 Production Capacity 160 to 200 kg Per Hour</p>	
	<p>Potato Cum Onion Peeler</p>	<p>Motor Capacity 0.5 HP. Single Phase Voltage 230 volts, 50 Hz 10 Kg Dimensions (L x B x H): 540 x 450 x 910 (mm) Machine Weight: 43 Kg</p>	
	<p>Potato Cum Onion Peeler</p>	<p>Production Capacity 160 to 200 kg Per Hour Motor Capacity 0.5 HP. Single Phase Voltage 230 volts, 50 Hz 20 Kg Dimensions (L x B x H): 710 x 675 x 1180 (mm) Machine Weight: 43 Kg</p>	
<p>Dosa Making Machine with Compressor https://youtube.com/shorts/mRADFyvo4Fk?feature=share</p>		<p>Dosa Production 350 to 400 dosa Per Hour Oothapam Production 325 to 350 Oothapam Per Hour Motor Capacity 1 HP. 3 Phase / Single Phase Voltage 230 volts, 50 Hz Dimensions (L x B x H): 1410 x 1410 x 1070 (mm) Batter Capacity: 30 Liter Oil Consumption: 0.75 Liter Per Hour Fuel Consumption (Gas): 1 Kg per hour</p>	
	<p>SS Coconut Scraper Single side</p>	<p>Motor Capacity 0.1 Hp, Single Phase Drive: Belt Drive Dimensions (L x B x H): 530 x 330 x 560 (mm)</p>	
	<p>Cutter mixer machine</p>	<p>Production Capacity: 90 to 100 Kg Per Hour Motor Capacity 2.0 Hp, Single Phase or 3.0 Hp 3 Phase Dimensions (L x B x H): 450 x 360 x 830 (mm) Drum Capacity: 3 Kg Machine weight: 41 Kg</p>	
	<p>IRG-80 Instant Rice Grinder</p>	<p>Motor 230 volts, 50 Hz 2.0 Hp, Single Phase or 3.0 Hp 3 Phase Dimensions (L x B x H): 980 x 400 x 1400 (mm) Machine weight: 116 Kg Variant: 80 Kg</p>	
<p>IRG-150 Instant Rice Grinder https://www.youtube.com/shorts/rLhrlpTYO4w</p>		<p>Motor 230 volts, 50 Hz 2.0 Hp, Single Phase or 3.0 Hp 3 Phase Dimensions (L x B x H): 980 x 400 x 1400 (mm) Machine weight: 116 Kg Variant: 150 Kg</p>	
<p>25kg Rice Washer with 1hp Pressure Pump</p>		<p>Machine Capacity: 25 Kg Water Pump: 0.5 Hp - 1 Ph Machine Weight: 21.6 Kg Time Per Batch: 15 min Dimensions (L x B x H): 840 x 560 x 940 (mm)</p>	
<p>50kg Rice Washer with 1hp Pressure Pump</p>		<p>Machine Capacity: 25 Kg Water Pump: 0.1 Hp - 1 Ph Machine Weight: 24 Kg Time Per Batch: 20 min Dimensions (L x B x H): 980 x 720 x 1130 (mm)</p>	
<p>Semi Automatic Vada Machine https://youtube.com/shorts/1UNg37hixqo?feature=share</p>		<p>Semi Automatic machine fully SS body, 300 to 500 vadas per/hr, per minute 20 strokes, Motor 1/4 hp, single phase, Vada size 30 to 60 gms vada according to adjustment, Vada kadai 22" Frying System & Vada unit,</p>	

	Medhuvada Fully Automatic Machine	<p>Body Fully Stainless Steel Per Minute - 20 Stokers (vada) Motor 1/2 Hp, Automatic Machine Frying System LPG, Conveyor Type (800 to 1000 Vadas per/hr)</p>																													
Quality control Equipments																															
	Visco Meter	<p>labman - Digital Viscometer 1 unit Specification : Measuring Range—20-2,000,000,Mpa.S, Speed—0.3,No Of Speed 8,No Of Standard Spindle – 4, Display – Lcd.</p>																													
	PH Meter	<p>Elico - Ph Meter Table Type - Elico Specification : Ph Meter Li120</p>																													
MOC63u	Moisture Meter	<p>Capacity: Max 60g, Min 0.02g Minimum readability: 0.001g, 0.01/0.1% (Selectable) Repeatability (*1): 0.15% (2g), 0.05% (5g), 0.02% (10g) Drying Heater: Straight type halogen heater Power: 400W Temperature range setting : 50-200°C (1°C increments) (There is a time restriction when exceeding 180°C.) Display: LCD with backlight Pan size: φ95mm Dimensions (WxDxH) mm: 202 × 336 × 157 Weight: Approx 4.2kg Operational temperature and humidity range: 5 to 40°C, 85%RH or lo</p>	 <table border="1" data-bbox="1084 741 1268 814"> <thead> <tr> <th colspan="4">MOCKU</th> </tr> <tr> <th>1st</th> <th>Measurement (g)</th> <th>Sample Weight (g)</th> <th>Moisture (%)</th> </tr> </thead> <tbody> <tr> <td>2nd</td> <td>21.94</td> <td>2.074</td> <td>01.86</td> </tr> <tr> <td>3rd</td> <td>21.87</td> <td>2.251</td> <td>01.62</td> </tr> <tr> <td>Average</td> <td></td> <td></td> <td>01.55</td> </tr> <tr> <td>Standard deviation</td> <td></td> <td></td> <td>0.05</td> </tr> <tr> <td>CV (%)</td> <td></td> <td></td> <td>0.40</td> </tr> </tbody> </table>	MOCKU				1st	Measurement (g)	Sample Weight (g)	Moisture (%)	2nd	21.94	2.074	01.86	3rd	21.87	2.251	01.62	Average			01.55	Standard deviation			0.05	CV (%)			0.40
MOCKU																															
1st	Measurement (g)	Sample Weight (g)	Moisture (%)																												
2nd	21.94	2.074	01.86																												
3rd	21.87	2.251	01.62																												
Average			01.55																												
Standard deviation			0.05																												
CV (%)			0.40																												